

# DRYFOOD ANTISTATIC FORM T12BDC



Suction and delivery hose suitable for powdery and granular dry food products.

## DESCRIPTION

### Tube

NBR, white, antistatic ( $R < 10^8 \Omega/m$ ), phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.2600, BFR recommendation XXI cat 4, DM 21.03.73 e seguenti, EUROPEAN REGLEMENT 1935/2004/CE

### Reinforcement

synthetic plies, galvanized wire helices, a/s wires to discharge static electricity

### Cover

wide corrugated, blue with black conductive stripe, cloth finish. Abrasion, ageing and ozone resistant


## TECHNICAL CHARACTERISTICS

**Temperature range :** -25°C / +80°C ( -13°F / +176°F )

**Norm :** ISO 1307 for dimensional tolerances



refer to guidelines for cleaning and sanitizing on Tudertechnica website



| Inside diameter |      | Outside diameter |      | Vacuum |       | Working pressure |       | Burst pressure |       | Appr. weight |          | Bending radius |      |
|-----------------|------|------------------|------|--------|-------|------------------|-------|----------------|-------|--------------|----------|----------------|------|
| [mm]            | [in] | [mm]             | [in] | [bar]  | [psi] | [bar]            | [psi] | [bar]          | [psi] | [kg/mt]      | [lbs/ft] | [mm]           | [in] |
| 80              | 3,15 | 97               | 3,82 | 0,9    | 13    | 6                | 90    | 18             | 270   | 2,91         | 1,96     | 210            | 8,27 |

Data refer to ambient temperature (20°C). Other diameters, wall thickness and pressure only on specific request.